

Work Order ID 159498***159498***

Page 1

Wednesday, April 12, 2017 11:39:24 AM

Item ID: D5079-1 Accept ***N900040100*** Setup Start ***NS1***
Revision ID: Stop ***NS2***
Item Name: Placard, EAPS
Start Date: 4/12/2017 Start Qty: 6.00 ***6*** Cust Item ID:
Required Date: 4/19/2017 Req'd Qty: 6.00 ***6*** Customer:
Reference:

Approvals: Process Plan: **DAS 13 9-89** Date: **APR 12 2017** Tooling: Date: Run Start ***NR1***
QC: Date: SPC (Y/N): Date: Stop ***NR2***

Sequence ID/ Work Center ID	Operation Description	Set Up/ Run Hours	Tool ID	Tool #	Plan Code	Accept Qty	Reject Qty	Reject Number	Insp. Stamp
Draw Nbr	Revision Nbr								
D5079	B								
100	PURCHASING	0.00							DAS 13 9-89
100									
Purchasing	Memo	0.00							
Purchasing	Issue P/O: 35946								
	MANUFACTURE D5079-1 PLACARD AS PER DWG D5079								
	Material release note is required								
110	Receive & Inspect for Damage & Mat'l Certs	0.00							
110									
Packaging	Memo	0.12							
Packaging	Ensure material release note is attached								
120	QC6- Inspect dimensions to drawing	0.00							
120									
QC	Memo	0.00							
Quality Control									DAS 38 9-89

APR 18 2017

Work Order ID 159498

Wednesday, April 12, 2017 11:39:24 AM

159498

Page 2

Item ID: D5079-1

Accept

N900040100

Setup Start

NS1

Revision ID:

Stop

NS2

Item Name: Placard, EAPS

Start Date: 4/12/2017 Start Qty: 6.00

6

Cust Item ID:

Required Date: 4/19/2017 Req'd Qty: 6.00

6

Customer:

Reference:

Approvals:

Process Plan:

Date:

Tooling:

Date:

Run Start

NR1

QC:

Date:

SPC (Y/N):

Date:

Stop

NR2Sequence ID/
Work Center IDOperation
DescriptionSet Up/
Run Hours

Tool ID

Tool #

Plan
CodeAccept
QtyReject
QtyReject
NumberInsp.
Stamp

130

Identify as per dwg & Stock Location:

5148

0.00

130

Packaging

Memo

0.06

Packaging

***ONE YEAR EXPIRED DATE FROM
RECEIVING: MAR 18 2018***6DAS
6
9-89

APR 18 2017

140

QC21- Final Inspection - Work Order Release

0.00

140

QC

Memo

0.60

Quality Control

17/4/19 88

APR 19 2017

Picklist Print

Wednesday, April 12, 2017 11:39:24 AM

Page 1

Work Order ID: 159498

159498

Parent Item: D5079-1

D5079-1

Parent Item Name: Placard, EAPS

Start Date: 4/12/2017

Required Date: 4/19/2017


Start Qty: 6.00

Required Qty: 6.00

Comments: IPP REV:A 14.06.18 AS PER DWG REV.A DD VERF:JLM

Component Item ID/ Item Name	Replacement Item ID	Mfg/ Purch	Bin Item	Primary Location	Last Location	Route Seq ID	Unit of Measure	Qty on Hand	Qty per Kit	Total Qty	Qty Issued	Date Issued	Status
D5079-1P		Purchased	No			100	Each	0.0000	1	6			
D5079-1P									**				
Placard, EAPS													

6x SP 17-4-18



B D5079-1 PLACARD

DAS
13
9-23
APR 12 2017
W/O: 139498

NOTES:

- 1) MATERIAL: RED LETTERING WITH WHITE BACKGROUND AND ADHESIVE BACK MANUFACTURED FROM 3M, 7MIL MASKING FILM #8522CP OR AVERY IPM #2031
- 2) FINISH: N/A
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: N/A
- 6) IDENTIFICATION: NONE
- 7) WEIGHT: LESS THAN 0.01 lbs

RELEASED
2016-05-30
16-586

APPROVED

B	UPDATED PLACARD TEXT	CC	16.01.18
A	NEW ISSUE	DB	14.03.18
REV.	DESCRIPTION	BY	DATE
DESIGN	DB	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	CC		
CHECKED	AK	DRAWING NO.	REV. B
MFG. APPR.	DD	D5079	SHEET 1 OF 1
APPROVED	DW	TITLE	SCALE
DE APPR.	DS	PLACARD	NTS
DATE	16.01.18	COPYRIGHT © 2014 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	



Dart Aerospace Ltd.
1270 Aberdeen Street
Hawkesbury, ON K6A 1K7
Tel: 613 632 9577
Fax: 613 632 1053

PURCHASE ORDER

Purchase Order ID PO35946

Purchase Order Date 4/12/2017

PO Print Date 4/12/2017

Page Number 2 of 2

Order From :

VC-STU001

STUDIO DE LETTRAGE 2001
210 MAIN WEST
HAWKESBURY, ON K6A 2H6
CA

Ship To : DART AEROSPACE LTD

1270 ABERDEEN
HAWKESBURY, ON K6A 1K7
CANADA

Contact Name

Vendor Phone 613 632 5449

Ship To Contact

Ship To Phone

Ship Via: Yours ppd

Ship Acct:

Buyer

Chantal Lavoie

Customer POID

Customer Tax #

10127-2607

Terms

Net 30

Currency

CAD

FOB

Destination-Collect

Line Total: \$80.00

4 D5079-1P ✓ Placard, EAPS ✓ 4/19/2017 FN 6.00 ✓
Yes
4/19/2017 Each

\$13.33 ✓ \$80.00

AS PER DWG D5079 REV. B
B159498

DAS
38
9-89

Line Total: \$80.00

5 71401-45 ✓ PROCUREMENT QUALITY CLAUSES ✓ 4/19/2017

1.00 ✓ \$0.00 \$0.00

Procurement Quality Clauses

A005 right of entry
A012 chemical and physical test report
A016 personnel qualification
A017 raw material identification (as applicable)
A026 certification of material conformance
A041 quality management system
A042 dart notification by supplier
A043 retention of quality document

No
4/19/2017

SP 7418

Line Total: \$0.00

PO Total: \$320.00

W
CL

Note: Terms & Condition of Purchasing(Suppliers) and Procurement Quality Clauses are an integral part of our AS9100 requirements. To learn in detail, please visit www.dartaerospace.com for further explanation.

Change Nbr: 3

Change Date: 4/12/2017

210 Main West
Hawkesbury, Ontario K6A 2H6
Canada

INVOICE

Invoice No.: 44096
Date: 04/17/2017
Ship Date:
Page: 1
Re: Order No.

Sold to:

Dart Aerospace Ltd

1270 Aberdeen
Hawkesbury, Ontario
K6A 1K7

Ship to:

Dart Aerospace Ltd

1270 Aberdeen
Hawkesbury, Ontario
K6A 1K7

Quantity	Description	Base Price	Disc. %	Unit Price	Amount
6	D3428-1P.	13.33		13.33	79.98
6	D3525-1P.	13.33		13.33	79.98
6	D4732-17P.	13.33		13.33	79.98
6	D5079-1P.	13.33		13.33	79.98
	PO#35946				
	Attn: Chantal				
	Subtotal:				319.92
	H - HST				41.60
	HST				
SP17-4-18 DAS 38 9-89 Thank you for your business / Merci de faire affaire avec nous					

Shipped By:	Tracking Number:	HST: 825007651RT0001	Total Amount	361.52
Comment: WO20037			Amount Paid	0.00
Sold By:			Amount Owing	361.52

******CERTIFICATE of CONFORMITY******

Customer:

Studio SL2

Purchase Order N°:

35946

Packing Slip N°:

W30# 20037

Part N°:

Serial N°:

Description:

D3428-1P, D3525-1P
D4732-17P, D5679-1P

Quantity:

6,6,6,6.

Certification:

We hereby certify that:

1. The above listed items were manufactured, repaired and/or inspected in accordance with applicable drawings and/or specifications;
2. All work was accomplished in accordance with the Dart Aerospace Purchase Order;
3. Results of all inspections, chemical or physical tests, as well as other evidence, which shows the acceptability of raw materials, parts and/or assembly components are on file and available for inspection at any time.

Authority:

Avery

APPROVAL:

Valerie Young

Signature:

Val

Title:

office administrator

DATE:

April 17, 2017.

Avery® IPM™ 2031

issued: 01/04/2005

Introduction

Avery® IPM™ 2031 is a high quality pressure-sensitive vinyl film, designed for use on wide format inkjet printers. Avery® IPM™ 2031 has excellent printing properties, allowing crisp print quality with bright and vibrant colours. Avery® IPM™ 2031 offers rapid ink drying and a water-resistant material. It combines good adhesion during its life and easy removal afterwards.

Description

Facefilm: 80-micron premium white calendered, topcoated vinyl.
Adhesive: removable, acrylic based
Backing paper: one side coated kraft paper, 140 g/m²

Features

- Excellent printability
- Vibrant and bright colours
- Crisp print quality
- Spray water resistant with specific pigmented inks
- Good adhesion, excellent removability
- Warranty on outdoor durability

Recommendations for use

A wide variety of full-colour graphics for indoor - and **short/medium term outdoor** applications such as posters, murals, displays, exhibition stands, vehicle graphics etc. Avery® IPM™ 2031 is suitable for application to a wide variety of substrates and will remove cleanly for up to 1 year after application.

IPM media should be handled with care as any surface contamination may affect the print quality. Media should be processed in an environment of 15-25°C and 30-70% relative humidity. After drying, the finished prints should be wrapped in polyethylene film and despatched flat or rolled with the printed side facing outwards. To protect prints against water, UV/light and abrasion, overlamination with a clear film is recommended. For specific details of Avery® DOL combinations, refer to "Technical Bulletin 5.3. Recommended combinations of Avery® Overlaminates and Avery® Digital Print Media"

Always test your combination of Avery® IPM™ medium, inkjet printer and inks prior to commercial use.

Compatibility

Avery® IPM™ 2031 is compatible with a broad selection of inkjet printers, when printing with pigmented, water based inks. For specific details refer to "Technical Bulletin 5.6 Avery Dennison Inkjet Print Media - Printer compatibility".

Durability:

Avery® IPM™ 2031 is warranted for outdoor use in conjunction with pigmented outdoor inks from HP, Encad and Colorspan. The warranted period varies from type of application and type of overlaminate from 18 months up to 5 years. For full details, see our Avery® IPM™ Outdoor warranty.



Physical properties

Features	Test method ¹	Results
Caliper, facefilm	ISO 534	80 µm
Gloss	ISO 2813, 20°	1%
Dimensional stability	DIN 30646	0.3 mm. max
Adhesion, initial	FINAT FTM-1, stainless steel	180 N/m
Adhesion, ultimate	FINAT FTM-1, stainless steel	260 N/m
Flammability		Self extinguishing
Accelerating ageing	DIN 53587, 500h exposure	No negative impact on film Performance
Shelf life	Stored at 22° C/50-55 % RH	2 years
Removability		up to 1 year
Not when applied to: Nitro-cellulose paints, ABS, Polystyrene, certain types of PVC		
Durability ²	Overlaminated with DOL 4300	5 years
	Overlaminated with DOL 1000, DOL 1100 with overlaps	3 years
	Overlaminated without overlaps for static applications only	2 years
	Without overlaminate and used for static, Non-abrasive application ONLY	18 months

Only when printed with ENCAD GO, HP and Colorspan pigmented inks and when properly applied in accordance with our application instructions. Only applicable for vertical exposure.

Temperature range

Features	Results
Application temperature	Minimum: +10°C
Service temperature	-20°C to +80°C

Important

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use. All technical data are subject to change. In case of any ambiguities or differences between the English and foreign versions of these Conditions, the English version shall be controlling.

Warranty

Avery® branded materials are manufactured under careful quality control and are warranted to be free from defect in material and workmanship. Any material shown to our satisfaction to be defective at the time of sale will be replaced without charge. Our aggregate liability to the purchaser shall in no circumstances exceed the cost of the defective materials supplied. No salesman, representative or agent is authorised to give any guarantee, warranty, or make any representation contrary to the foregoing. All Avery® branded materials are sold subject to the above conditions, being part of our standard conditions of sale, a copy of which is available on request.

1) Test methods

More information about our test methods can be found on our website.

2) Durability

The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased.

